

SV37 - 45T - AV

INDUSTRIAL VACUUM WITH INTEGRATED HOPPER



Easy Transportability

Efficent Filtration System

UniVac

Experience the power of the Mobile Suction Unit with an integrated hopper designed for heavy and continuous use. Its versatile transport options and efficient filtering system ensure optimal performance in demanding

environments.

- 1m3 Capacity Hopper with Manual or Automatic Unloading Options
- Polyester Felt Filter Bags and Safety Cartridges for Effective Filtration
- Automatic Timed System for Filter Cleaning with Reverse Flow Air Counter-Current System
- Level Probe for Full Container Detection and Machine Stoppage
- Configurable Power Supply Options for Versatile
 Operation
- ATEX 2014/34/EU Certification for Ex II 3 D Compliance.

Specification:

		SV 37 T	SV45 T	SV 37 TAV	SV 45 TAV
Power	kW – Hp	37-50	45-60	37-50	45 -60
Max. Airflow	m³/h	2.050	2.450	1.850	2.100
Max. Vacuum	mm/H ₂ O	5.000	5.000	7.000	7.000
Primary Filter	m ²	16	16	16	16
Safety Filter	m ²	10	10	10	10
Filter Cleaning System		"Reverse Flow			
Air Cooling Pump Filter	m²			4	4
Dust Capacity	m ³	1	1	1	1
Sizes	cm.	150 x 130 x h=350			
Weight	kg	2200	2.250	2.350	2.350







paul@ptc360solutions.co.uk